



Vierkant

Zweiflach

Passfedernut

<b>Vierkant</b>	SW [mm]	9	10	11	12	14	17					<b>PSR-E</b>
<b>Zweiflach</b>	SW [mm]	9	11									
	E [mm]	12	14									
<b>Vierkant</b>	SW [mm]	10	11	12	14	16	17	22				<b>PSQ-E</b>
<b>Zweiflach</b>	SW [mm]	9	11	14								
	E [mm]	12,1	14,1	18,1								
<b>Vierkant</b>	SW [mm]	10	11	12	14	16	17	19	22			<b>PSQ 103</b>
<b>Zweiflach</b>	SW [mm]	9	11	14	17							
	E [mm]	12,1	14,1	18,1	22,2							
<b>Passfeder-Nut</b> (DIN 6885/1 - J9)	d [mm]	10	12	14	16	18	20	22	23	24	25	
	b [mm]	3	4	5	5	6	6	6	8	8	8	
<b>Passfeder-Nut</b> Abmessungen für zöllige Wellenenden	d [mm]	12,7	15,88	19,05	22,2							
	b [mm]	3,2	4,8	4,8	4,8							
<b>Vierkant</b>	SW [mm]	11	12	14	16	17	19	22	24			<b>PSQ 203</b>
<b>Zweiflach</b>	SW [mm]	9	11	14	17	19	22					
	E [mm]	12,1	14,1	18,1	22,2	25,2	28,2					
<b>Passfeder-Nut</b> (DIN 6885/1 - J9)	d [mm]	14	16	18	20	22	24	26	28	30		
	b [mm]	5	5	6	6	6	8	8	8	8		
<b>Passfeder-Nut</b> Abmessungen für zöllige Wellenenden	d [mm]	12,7	15,88	19,05	22,2	28,58	31,75					
	b [mm]	3,2	4,8	4,8	4,8	6,38	6,38					
<b>Vierkant</b>	SW [mm]	14	16	17	19	22	24	27	36			<b>PSQ 503-1503</b>
<b>Zweiflach</b>	SW [mm]	9	11	14	17	19	22	27	36			
	E [mm]	12,1	14,1	18,1	22,2	25,2	28,2	36,2	48,2			
<b>Passfeder-Nut</b> (DIN 6885/1 - J9)	d [mm]	16	18	20	22	23	24	25	26	28	29	
	b [mm]	5	6	6	6	8	8	8	8	8	8	
	d [mm]	30	32	35	38	40	42					
	b [mm]	8	10	10	10	12	12					
<b>Passfeder-Nut</b> Abmessungen für zöllige Wellenenden	d [mm]	15,88	19,05	22,2	28,58	31,75	33,34	38	41,15			
	b [mm]	4,8	4,8	4,8	6,38	6,38	7,9	9,5	9,5			

Andere auf Anfrage möglich!

= Preis gemäß Preisliste

= Preis auf Anfrage